Aykos Antifreeze Protect -11 -40°C



Premixed radiator protection fluid

Product description and properties

Aykos Antifreeze Protect -11 -40°C is a silicate-containing coolant based on ethylene glycol that is free from amines, nitrites and phosphates. It offers excellent protection against frost, corrosion and overheating and is also ideally suited for light alloy engines.

Aykos Antifreeze Protect -11 -40°C provides:

- Free from amines, nitrites and phosphates
- Excellent protection against frost, rust and overheating
- Premixed with demineralised water, contains at least 60% antifreeze concentrate

Application

Aykos Antifreeze Protect -11 -40°C is premixed with demineralised water and contains at least 60% antifreeze concentrate. It can be used directly undiluted or further diluted with normal tap water if required. To ensure optimum corrosion protection, the concentration should not fall below 50%, especially in summer operation. A change of coolant is recommended after 5 years at the latest. If the engine manufacturer prescribes the use of a silicate-free coolant, the corresponding operating instructions (for example VW, Audi, Seat, Skoda, Ford, GM/Opel from 1997) must be observed.

Specifications / Recommendations

MB-325.0 & 325.2 Ford ESD-M97B94-A Saab 6901 599 MAN 324 NF Cummins 85T8 VW / Audi / Seat / Skoda / Porsche TL 774-C (G11) Opel GME L301 BMW GS 94000 MTU MTL 5048 Lada TTM VAZ 1.97.717-97 Volvo 128

Reference values

Aykos Antifreeze Protect -11 -40°C	unit	value
Density at 20°C	kg/m³	1085
Colour		blue
Stock point	°C	-40
Flashpoint	°C	>100
pH - value		8,4
Boiling point	°C	>145

Article no: 119670-XXX

We reserve the right to make changes to the technical data. Please observe the regulations of the machine manufacturer. For further information, please refer to the safety data sheet.

K2 Kfz-Ersatzteile Grosshandel GmbH

Grünbergstraße 40 D-47445 Moers

Telephone: +49 (0)2841-8827000

www.aykos.de info@aykos.de

EN-PDS 01.11.2024