

Aykos Hydro HVLP ISO VG 32



HVLP - Hydraulic oil to DIN 51524, Part 3

Product description and properties

Aykos Hydro HVLP ISO VG 32 is a hydraulic oil that impresses as a mineral oil-based high-performance hydraulic fluid with outstanding viscosity-temperature behaviour. The special additive combination improves corrosion protection, ageing resistance and wear protection, so that the requirements of DIN 51524 Part 3 are not only met but exceeded.

Aykos Hydro HVLP ISO VG 32 provides:

- Excellent high pressure and shear stability
- High viscosity index for optimum performance
- Compatibility with material coatings and sealing materials
- Reliable and easy filterability

Application

Aykos Hydro HVLP ISO VG 32 is a hydraulic oil that is particularly suitable as a pressurised fluid for outdoor use in year-round operation where temperatures fluctuate greatly. Typical applications include construction machinery, forklift trucks, scrap presses, machine tools and robots.

Specifications / Recommendations

DIN 51 524-2 (HM)

Denison HF0, HF1, HF2

Bosch Rexroth Fluid Rating List' RDE 90245

Reference values

Aykos Hydro HVLP ISO VG 32	unit	value	Method
ISO-VG class		32	DIN 51 519
Density at 15°C	kg/m ³	847	DIN 51 757
Kinematic viscosity at 40°C	mm ² /s	32,8	DIN 51 562
Kinematic viscosity at 100°C	mm ² /s	6,3	DIN 51 562
Viscosity index		147	DIN ISO 2909
Pourpoint	°C	-36	DIN ISO 3016
Flashpoint	°C	205	DIN ISO 2592

Article no: 119753-XXX

We reserve the right to make changes to the technical data.
Please observe the regulations of the machine manufacturer.
For further information, please refer to the safety data sheet.

K2 Kfz-Ersatzteile Grosshandel GmbH
Grünbergstraße 40
D-47445 Moers
Telephone: +49 (0)2841-8827000

www.aykos.de
info@aykos.de