Aykos PS 10W-40



High-performance low-friction engine oil for car engines

Product description and properties

Aykos PS 10W-40 is a semi-synthetic engine oil for petrol and diesel car engines, including those with turbochargers. It reduces fuel and oil consumption, protects against deposits and ensures reliable wear protection. Its viscosity range makes it suitable for all-season use and ensures clean engines under demanding conditions.

Aykos PS 10W-40 provides:

- Reliable wear protection
- Protection against deposits and blockages
- Excellent lubricating properties
- All-season use due to wide viscosity range
- Extended service life due to modern oxidation inhibitors

Application

Aykos PS 10W-40 is ideal for modern petrol and diesel car engines, both with and without turbochargers. It ensures reliable protection and performance under difficult operating conditions and is ideal for all-season use.

Specifications / Recommendations

ACEA A3 / B4 API SN / CF VW 505 00 Renault RN 0700 PSA B71 2296 MB 229.1

Reference values

Aykos PS 10W-40	unit	value	Method
Density at 15°C	kg/m³	857	DIN 51 757
Viscosity at 40°C	mm²/s	96,2	DIN 51 562
Viscosity at 100°C	mm²/s	15,1	DIN 51 562
Viscosity Index		165	DIN ISO 2909
Dynam. viscosity at -25°C	mPa.s	4180	DIN 51 377
HTHS-Viscosity at 150°C	mPa.s	min. 3,5	ASTM D5481
Pourpoint	°C	-39	DIN ISO 3016
Flashpoint	°C	226	DIN ISO 2592
TBN	mg KOH/g	10,5	DIN ISO 3771

Article no: 119002-XXX

We reserve the right to make changes to the technical data. Please observe the regulations of the machine manufacturer. For further information, please refer to the safety data sheet.

K2 Kfz-Ersatzteile Grosshandel GmbH

Grünbergstraße 40 D-47445 Moers

Telephone: +49 (0)2841-8827000

www.aykos.de info@aykos.de

EN-PDS 01.07.2025