

Aykos PS 15W-40



High-performance-engine oil for car engines

Product description and properties

Aykos PS 15W-40 is a versatile multigrade engine oil with an optimised formulation that reduces fuel and oil consumption. It is suitable for year-round use and prevents deposits and blockages in the oil circuit thanks to its dispersing properties. Modern oxidation inhibitors extend the service life of the oil, while effective wear protection supports the service life of the engine.

Aykos PS 15W-40 provides:

- All-season use thanks to wide viscosity range
- Reduced fuel and oil consumption thanks to optimised formulation
- Prevents deposits and protects the engine from overheating.
- Extends the service life of the engine thanks to effective wear protection.
- Longer oil life thanks to modern oxidation inhibitors.

Application

Aykos PS 15W-40 can be used in petrol and diesel car engines, including vehicles with catalytic converters and with or without turbochargers. Its use is particularly recommended in modern car engines, even under demanding operating conditions.

Specifications / Recommendations

ACEA A3 / B4
API SN / CF
MB-229.1
VW 505 00

Reference values

Aykos PS 15W-40	unit	value	Method
Density at 15°C	kg/m ³	873	DIN 51 757
Viscosity at 40°C	mm ² /s	115	DIN 51 562
Viscosity at 100°C	mm ² /s	15,3	DIN 51 562
Viscosity Index		140	DIN ISO 2909
Dynam. viscosity at -20°C	mPa.s	5380	DIN 51 377
Pourpoint	°C	-42	DIN ISO 3016
Flashpoint	°C	230	DIN ISO 2592
TBN	mg KOH/g	10,1	DIN ISO 3771

Article no: 119302-XXX

We reserve the right to make changes to the technical data.
Please observe the regulations of the machine manufacturer.
For further information, please refer to the safety data sheet.

K2 Kfz-Ersatzteile Grosshandel GmbH
Grünbergstraße 40
D-47445 Moers
Telefon: +49 (0)2841-8827000

www.aykos.de
info@aykos.de