Aykos PS 5W-30



HC-Synthese high-performance low-friction engine oil for car engines

Product description and properties

Aykos PS 5W-30 is a HC synthetic low-friction engine oil developed for petrol and diesel car engines. It is made from high-quality synthetic base oils and state-of-the-art additive technology to ensure optimum engine performance and efficiency.

Aykos PS 5W-30 provides:

- The optimised formulation reduces fuel and oil consumption.
- The efficient dispersing capacity prevents deposits and blockages in the oil circuit, keeping the engine clean.
- Outstanding low-temperature properties enable problem-free cold starting and rapid oiling through in frosty conditions.
- Modern oxidation inhibitors extend the service life of the engine oil.
- Reliable wear protection ensures a long engine service life.

Application

Aykos PS 5W-30 is ideal for use in modern car engines with and without turbochargers and is ideal for all operating conditions such as motorway and city traffic.

Specifications / Recommendations

ACEA A3 / B4 API SP / CF

Reference values

Aykos PS 5W-30	unit	value	Method
Density at 15°C	kg/m³	850	DIN 51 757
Viscosity at 40°C	mm²/s	71	DIN 51 562
Viscosity at 100°C	mm²/s	12	DIN 51 562
Viscosity Index		166	DIN ISO 2909
Dynam. viscosity at -30°C	mPa.s	6480	DIN 51 377
HTHS-viscosity at 150°C		min. 3,5	ASTM D5481
Pourpoint	°C	-42	DIN ISO 3016
Flashpoint	°C	228	DIN ISO 2592
TBN	mg KOH/g	10,6	DIN ISO 3771

Article no: 119102-XXX

We reserve the right to make changes to the technical data. Please observe the regulations of the machine manufacturer. For further information, please refer to the safety data sheet.

K2 Kfz-Ersatzteile Grosshandel GmbH

Grünbergstraße 40 D-47445 Moers

Telephone: +49 (0)2841-8827000

www.aykos.de info@aykos.de

EN-PDS 01.11.2024