# Aykos SHPD-Multi 10W-40



### High-performance low-friction engine oil

### **Product description and properties**

**Aykos SHPD-Multi 10W-40** is a high-performance engine oil based on mineral base oils and hydrocracked synthetic oil. In combination with special additives, it fulfils the requirements of modern engine generations, both for diesel engines and petrol engines. It is particularly suitable for highly developed engines with exhaust gas turbochargers or lean-burn operation, which place high demands on the lubricant.

## Aykos SHPD-Multi 10W-40 provides:

- Outstanding wear protection ensures a long service life for the motor.
- Trouble-free operation even under extreme operating conditions.
- Optimum oxidation stability minimises premature oil ageing, even at high temperatures.
- Maximum oil change intervals specified by the manufacturer are reliably achieved.

## **Application**

**Aykos SHPD-Multi 10W-40** is used in modern diesel and petrol engines and is especially suitable for engines with exhaust gas turbochargers or lean-burn operation.

## **Specifications / Recommendations**

ACEA E7 API CI-4 / CF / SL DDC 93K215 Jaso DH-1 MAN M 3275 MTU Type 2 VOLVO VDS-3 Caterpillar ECF-1a & ECF-2 Cummins CES 20077 / 20078 Global DHD-1 Mack EO-M Plus & EO-N MB-228.3 Renault RLD / RLD2 DEUTZ DQC III-18

#### **Reference values**

Aykos SHPD-Multi 10W-40	unit	value	Method
Density at 15°C	kg/m³	860	DIN 51 757
Viscosity at 40°C	mm²/s	99,6	DIN 51 562
Viscosity at 100°C	mm²/s	14,6	DIN 51 562
Viscosity Index		152	DIN ISO 2909
Dynam. viscosity at -25°C	mPa.s	5980	DIN 51 377
Pourpoint	°C	-39	DIN ISO 3016
Flashpoint	°C	234	DIN ISO 2592
TBN	mg KOH/g	11,3	DIN ISO 3771

Article no: 119000-XXX

We reserve the right to make changes to the technical data. Please observe the regulations of the machine manufacturer. For further information, please refer to the safety data sheet.

K2 Kfz-Ersatzteile Grosshandel GmbH

Grünbergstraße 40 D-47445 Moers

Telephone: +49 (0)2841-8827000

www.aykos.de info@aykos.de

EN-PDS 01.11.2024