

Aykos SHPD-Multi 15W-40



High-performance multigrade engine oil

Product description and properties

Aykos SHPD-Multi 15W-40 is a high-performance engine oil with SHPD character which, thanks to its advanced additive technology, fulfils the high requirements of both highly charged diesel engines and powerful petrol engines. This makes it ideal for mixed-fleet operation.

Aykos SHPD-Multi 15W-40 provides:

- Extended oil change intervals thanks to high TBN reserve in accordance with manufacturer specifications.
- Effective protection against 'bore polishing' and engine wear.
- Outstanding thermal and oxidative stability prevents sludge and deposit formation.
- Reliable protection against oil ageing even at high operating temperatures.

Application

Aykos SHPD-Multi 15W-40 is highly recommended for use in vehicle fleets in long-distance transport and city bus operations. It was specially developed for heavy-duty engines and is ideal for mixed fleets with diesel and petrol engines.

Specifications / Recommendations

ACEA E7
API CI-4 / SL
DDC 93K215
VOLVO VDS-3
Mack EO-M Plus / EO-N
MB-228.3
Renault RLD1 / RLD2

Caterpillar ECF-1a / ECF-2
Cummins CES 20077 / 20078
Global DHD-1
JASO DH-1
MAN M 3275
MTU Typ 2.0
Deutz DQC III-10

Reference values

Aykos SHPD-Multi 15W-40	unit	value	Method
Density at 15°C	kg/m ³	860	DIN 51 757
Viscosity at 40°C	mm ² /s	93	DIN 51 562
Viscosity at 100°C	mm ² /s	14,5	DIN 51 562
Viscosity Index		162	DIN ISO 2909
Dynam. viscosity at -20°C	mPa.s	3720	DIN 51 377
Pourpoint	°C	-42	DIN ISO 3016
Flashpoint	°C	232	DIN ISO 2592
TBN	mg KOH/g	11,3	DIN ISO 3771

Article no: 119300-XXX

We reserve the right to make changes to the technical data.
Please observe the regulations of the machine manufacturer.
For further information, please refer to the safety data sheet.

K2 Kfz-Ersatzteile Grosshandel GmbH
Grünbergstraße 40
D-47445 Moers
Telephone: +49 (0)2841-8827000

www.aykos.de
info@aykos.de