

Aykos SHPD-Multi 20W-50



High-performance multigrade engine oil

Product description and properties

Aykos SHPD-Multi 20W-50 is a high-performance engine oil with SHPD properties that fulfils the requirements of modern heavy-duty diesel engines as well as high-performance petrol engines thanks to its advanced additive technology. It is ideal for mixed fleet operation, especially in regions where the viscosity 20W50 is necessary or recommended due to the climatic conditions.

Aykos SHPD-Multi 20W-50 provides:

- Reduced oil ageing even at high temperatures.
- Excellent thermal-oxidative stability minimises sludge and deposit formation.
- Effective prevention of 'bore polishing'.
- High TBN reserve enables maximum oil change intervals in accordance with manufacturer specifications.

Application

Aykos SHPD-Multi 20W-50 is ideal for use as a diesel engine oil in long-distance transport fleets, including lorries and buses, as well as in construction vehicles.

Specifications / Recommendations

ACEA E7

API CI-4 / SL

MTU Typ 2

MB-228.3 & 229.1

MAN M 3275

Reference values

Aykos SHPD-Multi 20W-50	unit	value	Method
Density at 15°C	kg/m ³	882	DIN 51 757
Viscosity at 40°C	mm ² /s	147,5	DIN 51 562
Viscosity at 100°C	mm ² /s	17,7	DIN 51 562
Viscosity Index		132	DIN ISO 2909
Dynam. viscosity at -15°C	mPa.s	5900	DIN 51 377
Pourpoint	°C	-33	DIN ISO 3016
Flashpoint	°C	234	DIN ISO 2592
TBN	mg KOH/g	10,8	DIN ISO 3771

Article no: 119350-XXX

We reserve the right to make changes to the technical data.
Please observe the regulations of the machine manufacturer.
For further information, please refer to the safety data sheet.

K2 Kfz-Ersatzteile Grosshandel GmbH
Grünbergstraße 40
D-47445 Moers
Telephone: +49 (0)2841-8827000

www.aykos.de
info@aykos.de