

Aykos UNI SYNTH 5W-40



High-performance low-friction engine oil

Product description and properties

Aykos UNI SYNTH 5W-40 is an engine oil made from high-quality synthetic technology. With advanced additives, it offers high thermal stability, excellent oxidation protection and optimum flow properties. It fulfils the requirements of modern engines and supports efficiency and longevity.

Aykos UNI SYNTH 5W-40 provides:

- High protection against wear and corrosion as well as very good dispersing behaviour for clean engines and a long service life.
- Optimised high-temperature viscosity reduces emissions and meets the latest requirements.
- Can be used all year round thanks to stable temperature-viscosity behaviour and reliable performance even with long oil change intervals.
- Excellent cold start behaviour down to -30°C with guaranteed oil and fuel savings.

Application

Aykos UNI SYNTH 5W-40 is a high-performance, low-friction engine oil developed for petrol and diesel car engines. It is ideal for modern, performance-enhanced injection engines as well as all petrol and turbo engines.

Specifications / Recommendations

ACEA A3 / B4
API SN / CF
Porsche A40
Fiat 9.55535-M2
VW 502 00 / 505 00

BMW LL 98
Renault RN 0710 / 0700
Opel GM-LL-B-025
PSA B71 2296
MB-229.3

Reference values

Aykos UNI SYNTH 5W-40	unit	value	Method
Density at 15°C	kg/m ³	853	DIN 51 757
Viscosity at 100°C	mm ² /s	14,5	DIN 51 562
Viscosity Index		170	DIN ISO 2909
Dynam. viscosity at -30°C	mPa.s	6500	DIN 51 377
Pourpoint	°C	-42	DIN ISO 3016
Flashpoint	°C	226	DIN ISO 2592
TBN	mg KOH/g	10,3	DIN ISO 3771

Article no: 119200-XXX

We reserve the right to make changes to the technical data.
Please observe the regulations of the machine manufacturer.
For further information, please refer to the safety data sheet.

K2 Kfz-Ersatzteile Grosshandel GmbH
Grünbergstraße 40
D-47445 Moers
Telephone: +49 (0)2841-8827000

www.aykos.de
info@aykos.de